

FSDC® (Model LHL3933BKA) Polymer Lever Hammer Lock Instruction Sheet

WARNING!

NEVER INSTALL ON A LOADED FIREARM

Failure to follow any of these instructions can result in death or serious injury to you or those around you. Putting a Lever Hammer Lock on a loaded firearm OR loading a firearm that has a Lever Hammer Lock on may result in serious injury or death!

- Prior to installing the Lever Hammer Lock, read the Owner's Manual supplied with your firearm before loading, handling, or operating.
- Store firearms and ammunition separately and securely. Keep firearms and ammunition out of the reach of children.
- This lock may be cut or defeated by a determined individual and may not prevent intentional misuse of a firearm.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. Use of this product, including its use after discharging firearms in poorly ventilated areas, cleaning firearms, or handling ammunition may result in exposure to lead. Have adequate ventilation at all times and wash hands thoroughly after handling this product.

NOTICE: Firearm Safety Devices Corporation does not guarantee that this product will fit all Lever Action Rifles. It is designed to lock the Loop Lever/Trigger Guard from being opened and closed and opening the action. Additionally, the Hammer is blocked from being pulled back. Note – If this lock was on the firearm when you purchased it, you should replace it with the firearm safety device provided by the manufacturer (if supplied). Firearm Safety Devices Corporation is not liable for incidental or consequential damages.

INSTALLATION INSTRUCTIONS

1. Note – If your firearm was originally packaged with a specific Firearm Safety Device and/or the firearm's Owner's Manual refers to a specific Firearm Safety Device, use that device to secure your firearm.
2. If provided, place the firearm's safety mechanism in the "ON" or "SAFE" position. Keep the firearm pointed in a safe direction while handling the firearm and when installing or removing the Lever Hammer Lock.
3. Unload all ammunition from the firearm as detailed in the firearm's Owner's Manual.
4. Visually and physically inspect the Receiver (Loading Port, Breech Bolt, and Ejection Port) and Magazine Tube (if applicable) to ensure that the firearm is completely unloaded.
5. To open the Lever Hammer Lock, unscrew the locking bolt by turning the provided key counter-clockwise until the two sides can be pulled apart. (See Picture #1)
6. With the firearm pointed in a safe direction and the Loop Lever/Trigger Guard in the closed position against the bottom of the Buttstock, feed one side of the Lever Hammer Lock through the Finger Lever. (See Picture #2)
7. Close the 2 sides of the Lever Hammer Lock above the Buttstock and position the lock's head behind the Hammer. (See Picture #3)
8. While holding the top of the Lever Hammer Lock closed and behind the Hammer, take the provided key and turn the locking bolt clockwise until the two sides of the lock's head are firmly against one another and the Lever Hammer Lock will not slide backwards. (See Picture #4)
9. Test the Lever Hammer Lock for fit and proper application by attempting to open the Loop Lever/Trigger Guard. If the Loop Lever/Trigger Guard opens, remove the Lever Hammer Lock and repeat Step 5. If the Hammer can be pulled back or the Lever Hammer Lock can be easily moved backwards and away from the Hammer, stop and Repeat Step 5.
10. Store the provided key in a separate and secure location away from the locked firearm.

Picture #1



Picture #2



Picture #3



Picture #4

